Compressed Air and Industrial Motors Worksheet



TAKE CHARGE

Before you start

Instructions: Complete all relevant information for your project. Include with completed final application package.

All rebates are paid per unit and are capped at 30 percent of project's total cost.

Project Information

Questions? Call 888-261-4567.

Submit your application

The following documents must accompany the Compressed Air and Industrial Motors Worksheet in a complete application:

- Rebate application
- Equipment spec sheet
- Itemized invoice showing model number
- W9 for payee
- Copy of latest electric bill

Retrofit		
ZIP (project location):	Estimated/Actual In:	stall Date:
2 Building Type		
Assembly Auto-Related Convenience Store Data Center Education - Community College Education - Primary School Education - University Education - Secondary School Grocery Gymnasium Health/Medical - Hospital	 □ Health/Medical - Nursing Home □ Industrial/Manufacturing - 1-Shift □ Industrial/Manufacturing - 2-Shift □ Industrial/Manufacturing - 3-Shift □ Industrial/Manufacturing - Biotech/High - Tech □ Institutional/Public Service □ Lodging - Hotel □ Lodging - Motel □ Multi-Family (Common Areas) □ Museum/Library 	Office - Large Office - Small Religious Worship/Church Restaurant - Fast-Food Restaurant - Sit-Down Retail - Multi-story Large Retail - Single-story Large Retail - Small Storage - Conditioned Warehouse Warehouse - Refrigerated

Business Name:				
Contact Name:	Phone:			
Business Address:				
City:	State:	ZIP:		

4 Air Nozzles for Air Compressors

Cost			
Compressor Control Type	Reciprocating - On/Off Reciprocating - Load/Unload Screw - Load/Unload Screw - Inlet Modulation Screw - Inlet Modulation w/ Unloading Screw - Variable Displacement Screw - VFD	□ Reciprocating - On/Off □ Reciprocating - Load/Unload □ Screw - Load/Unload □ Screw - Inlet Modulation □ Screw - Inlet Modulation w/ Unloading □ Screw - Variable Displacement □ Screw - VFD	□ Reciprocating - On/Off □ Reciprocating - Load/Unload □ Screw - Load/Unload □ Screw - Inlet Modulation □ Screw - Inlet Modulation □ Screw - Inlet Modulation □ Screw - Variable Displacement
Nozzle Size	□ 1/4" □ 1/8"	□ 1/4" □ 1/8"	1,44"
Facility Operation Schedule	 □ 1-Shift 5 Days per Week □ 2-Shift 5 Days per Week □ 3-Shift 5 Days per Week □ 24/7 	☐ 1-Shift 5 Days per Week☐ 2-Shift 5 Days per Week☐ 3-Shift 5 Days per Week☐ 24/7	1-Shift 5 Days per Week 2-Shiff 5 Days per Week 3-Shiff 5 Days per Week 3-Shiff 5 Days per Week 24/7
Efficient Nozzle CFM			
Model #			
Manufacturer			
Quantity installed			
Date Installed			

S No-Loss Condensate Drain

Cost			
Facility Operation Schedule	□ 1-Shiff 5 Days per Week □ 2-Shiff 5 Days per Week □ 3-Shiff 5 Days per Week □ 24/7	☐ 1-Shiff 5 Days per Week☐ 2-Shiff 5 Days per Week☐ 3-Shiff 5 Days per Week☐ 2-4/7☐ 2-4/7	1-Shift 5 Days per Week 2-Shift 5 Days per Week 3-Shift 5 Days per Week 24/7
Compressor Control Type and Storage Volume	Reciprocating - On/Off Reciprocating - Load/Unload Screw - Load/Unload Screw - Inlet Modulation Screw - Inlet Modulation Screw - Inlet Modulation w/ Unloading Screw - Variable Displacement	Reciprocating - On/Off Reciprocating - Load/Unload Screw - Load/Unload Screw - Inlet Modulation Screw - Inlet Modulation Screw - Inlet Modulation w/ Unloading Screw - Sariable Displacement Screw - Variable Displacement	Reciprocating - On/Off Reciprocating - Load/Unload Screw - Load/Unload Screw - Inlet Modulation Screw - Inlet Modulation w/ Unloading Screw - Strew - Inlet Modulation w/ Unloading Screw - Variable Displacement
Compressor CFM or HP			
Model#			
Manufacturer			
QuantityInstalled			
Date Installed			

6 VFD Air Compressor

Date installed	Manufacturer	Mode!#	Operating Schedule	Compressor Motor Size (HP) Equipment Cost	Equipment Cost
			 □ 1-Shift 5 Days per Week □ 2-Shift 5 Days per Week □ 3-Shift 5 Days per Week □ 24/7 		
			1-Shift 5 Days per Week 2-Shift 5 Days per Week 3-Shift 5 Days per Week 3-Shift 5 Days per Week		

Variable Frequency/Speed Process Pumps and Fans

Quantity Installed	ed Manufacturer	Model #	Efficient Motor HP Eligibility limited for certain size motors - See Appendix for motor size requirements	Existing Motor Type	Existing Flow Control Type	Cost
				□ Fan	 □ Bypass Valve (Pumps) □ Discharge Damper (Fan) □ Eddy Current Drive (Fans or Pumps) □ Outlet Control Valve (Pumps) □ Outlet Damper (Forward-Curved Fan) □ Torque Converter (Pumps) □ Torque Converter (Pumps) □ VFD (Fans or Pumps) □ Motor Horsepower 	
				□ Fan	Bypass Valve (Pumps) Discharge Damper (Fan) □ Eddy Current Drive (Fans or Pumps) □ Outlet Control Valve (Pumps) □ On/Off (Fans or Pumps) □ Torque Converter (Pumps) □ Torque Converter (Pumps)	

Compressed Air and Industrial Motors Worksheet Appendix

VFD Process Pumps and Fans

Measure Description: Variable Frequency Drives (VFDs) control the speed of a motor to match flow demands.

How It Saves Energy: When used in place of traditional controls such as throttling or bypass valves in applications for which loads vary, VFDs can be highly effective at cutting energy costs.

Eligibility: This measure applies only to process pumps and fans. Controls on pumps or fans used for space conditioning do not qualify. VFD speed must be controlled automatically by differential pressure, flow, temperature, or another relevant input.

Air Nozzles for Air Compressors

Measure Description: This measure applies to the replacement of an inefficient, stationary, non-air entraining air nozzle in an industrial application.

How It Saves Energy: By entraining and amplifying atmospheric air into a stream, air-entraining air nozzles use less compressed air to do the same job as conventional air nozzles. Air-entraining nozzles can also reduce noise in systems with air at pressures greater than 30 psig.

Eligibility: Air-entraining air nozzles must replace an open copper tube (of 1/8" or 1/4" orifice diameter) with an energy-efficient air-entraining air nozzle that uses less than 15 CFM at 100 psi.

No-Loss Condensate Drains

Measure Description: This measure applies to the installation of new no-loss condensate drains in a compressed air system that prevent compressed air from leaving the system when condensate is drained.

How It Saves Energy: Water that is condensed out of a compressed air system (typically by refrigerated air dryers) must be drained. Many condensate drains are controlled by a timer that operates the drain for a fixed amount of time on regular intervals regardless of condensate levels. When drains open, compressed air escapes without doing any purposeful work in the system. In a no-loss condensate drain system, a sensor monitors condensate level, opens the drain valve when condensate needs to be drained, and closes before compressed air can escape.

Eligibility: To be eligible, no-loss condensate drains must replace standard condensate drains operated by a timer-controlled solenoid valve.

VFD for Air Compressor

Measure Description: VFD air compressor closely matches air demand with production by varying compressor speed to match production.

How It Saves Energy: Compared to load/no load machines, VFD air compressors save energy at part-load conditions.

Eligibility: Measure applies to new and replacement air compressors having VFD controls. Machine must be more than 10 HP and no more than 40 HP. It must be installed in a facility of at least 2-shifts.

The following conditions must also be met for the project to be eligible:

- The VFD must be used in conjunction with a process (non-HVAC) pump or fan application.
- · Redundant or back-up units do not qualify.
- Routine replacement of existing VFDs does not qualify.
- VFD speed must be automatically controlled by differential pressure, flow, temperature, or another variable signal.
- The system controlled must have significant load diversity that will
 result in savings through motor speed variation. Conditions in which
 the motor is loaded consistently above 80% or consistently below
 30% are ineligible, as these operating conditions may not realize
 sufficient savings from a VFD to qualify for an incentive.
- Motors must operate at least 3700 hours per year. Copies of invoices must list the drive's capacity (in motor HP)
- Eligible controlled motor size depends on type of load and existing control, as follows:

Load Type	Replaced Control Type	Minimum Motor Size
Pump	Bypass Valve	2 hp
Pump	Outlet Control	5 hp
Pump or Fan	Eddy Current Drive	10 hp